

Rivendell A.Homer Hilsen geometry chart

Size	BB Drop mm	TT Upslope degrees	Rear Hub Space mm	Standover at mid TT cm	ST angle degrees	HT angle degrees	Rake cm	Top Tube cm	Chain stay cm	Wheel size mm	Recommended min. tire radius mm	Recommended max. tire radius mm	Effective brake reach mm	Brake style
57	80	1.5	135	83.1	72	72	5.2	57	45	622/700c	345/700x32	360/700x43	65	CP/SP
59	80	1.5	135	85	72	72	5.2	58	45	622/700c	345/700x32	360/700x43	65	CP/SP
61	80	1.5	135	86.9	72	72	5.2	59	45	622/700c	345/700x32	360/700x43	65	CP/SP
63	80	1.5	135	88.8	72	72	5.2	60.5	45	622/700c	345/700x32	360/700x43	65	CP/SP
65	80	1.5	135	90.7	72	72.5	4.75	62.5	45	622/700c	345/700x32	360/700x43	65	CP/SP
67	70	1.5	135	92.6	72	72.5	4.75	64.5	45	622/700c	345/700x32	360/700x43	65	CP/SP
72	65	1.5	135	92.6	72	72.5	4.75	66	45	622/700c	345/700x32	360/700x43	65	CP/SP