

## Rivendell Atlantis geometry chart

Size	BB Drop mm	TT Upslope degrees	Rear Hub Space mm	Standover at mid TT cm	ST angle degrees	HT angle degrees	Rake cm	Top Tube cm	Chain stay cm	Wheel size mm	Recommended min. tire radius mm	Recommended max. tire radius mm	Effective brake reach mm	Brake style
47	48	2.5	135	71.2	72.5	71	4.5	52	44	559/26 in.	310/26x1.25	328/26x1.85	n/a	Cantilever
51	48	2.5	135	77	72.5	72	4	53.5	44	559/26 in.	310/26x1.25	340/26x2.35	n/a	Cantilever
53	48	2.5	135	78.9	72.5	72	4	55	44	559/26 in.	310/26x1.25	340/26x2.35	n/a	Cantilever
54.5	48	2.5	135	80.8	72	72	4	56	44	559/26 in.	310/26x1.25	340/26x2.35	n/a	Cantilever
56	48	2.5	135	81.7	72	72	4	57	44	559/26 in.	310/26x1.25	340/26x2.35	n/a	Cantilever
58	80	2.5	135	83.2	72	72	4.5	58.5	45.5	622/700c	345/700x32	365/700x55	n/a	Cantilever
61	80	2.5	135	85.1	72	72	4.5	59	45.5	622/700c	345/700x32	365/700x55	n/a	Cantilever
64	80	2.5	135	87	72	72	4.5	60	45.5	622/700c	345/700x32	365/700x55	n/a	Cantilever
66	80	2.5	135	88.9	72	72	4.5	61	45.5	622/700c	345/700x32	365/700x55	n/a	Cantilever
68	80	2.5	135	90.8	72	72	4.5	62	45.5	622/700c	345/700x32	365/700x55	n/a	Cantilever